

SUPERtrol-I LE

Economical Flow Totalizer, Ratometer and Batcher

Features

- EZ Setup Feature
- Setup Diskette
- Advanced Batching Features
- Menu Selectable Hardware Features
- Two Line LCD or VFD Display
- NEW! - 0-20mA or 4-20mA Analog Output
- NEW! - Attractive Wall Mount Enclosure
- Isolated Pulse Output Standard
- RS-232 Port Standard, RS-485 Optional
- Advanced Printing Capabilities
- Data Logging & Modem Remote Metering Support
- DIN Enclosure with Two Piece Connectors
- DDE Server & HMI Software Available

Description:

The SUPERtrol-I LE Flow Computer satisfies the instrument requirements for a variety of pulse producing flowmeter types in liquid applications.

The alphanumeric display shows measured and calculated parameters in easy to understand format. Single key direct access to measurements and display scrolling is supported. An EZ Setup feature rapidly guides the user through the basic setup.

The SUPERtrol-I LE can be programmed for rate/total indication or batching. The various pulse inputs and outputs can be "soft" assigned to meet a variety of common application needs. The user "soft selects" the usage of each feature while configuring the instrument. A 0-20mA or 4-20mA analog output is standard.

The user can assign the standard RS-232 Serial Port for data logging, transaction printing, or for connection to a modem for remote meter reading. An optional RS-485 serial port using Modbus RTU protocol is available.

A Service or Test mode is provided to assist the user during start-up system check out by monitoring inputs and exercising outputs. The system setup can also be printed.

Specifications:


Environmental

Operating Temperature: 0°C to +50°C
Storage Temperature: -40°C to +85°C
Humidity: 0-95% Non-condensing
Materials: U.L. approved

Listing: UL/C-UL Listed (File No. E192404), CE Compliant

Display

Type: 2 lines of 20 characters
Types: Backlit LCD and VFD ordering options
Character Size: 0.3" nominal
User programmable label descriptors and units of measure



Keypad

Keypad Type: Membrane Keypad
Keypad Rating: Sealed to Nema 4
Number of keys: 16

Enclosure

Size: See Dimensions
Depth behind panel: 6.5" including mating connector
Type: DIN
Materials: Plastic, UL94V-0, Flame retardant
Bezel: Textured per matt finish

Power Input

The factory equipped power option is internally fused. An internal line to line filter capacitor and MOV are provided for added transient suppression.

110 VAC Power Option: 85 to 127 Vrms, 50/60 Hz
220 VAC Power Option: 170 to 276 Vrms, 50/60 Hz
DC Power Option:
12 VDC (10 to 14 VDC)
24 VDC (14 to 28 VDC)

Flow Inputs:

Pulse Inputs:

Number of Flow Inputs: one (single or quadrature)
Input Impedance: 10 K Ω nominal
Pullup Resistance: 10 K Ω to 5 VDC (menu selectable)
Pull Down Resistance: 10 K Ω to common
Trigger Level: (menu selectable)

High Level Input
Logic On: 3 to 30 VDC
Logic Off: 0 to 1 VDC
Low Level Input (mag pickup)
Sensitivity:
10 mV or 100 mV

Minimum Count Speed:
User selectable (as low as 1 pulse/99 seconds)
Maximum Count Speed:
Selectable: 40 Hz, 3000 Hz or 20kHz
Overvoltage Protection: 50 VDC
Linearization: Average K or 16 Point linearization with separate forward and reverse tables

Control Inputs

Number of Inputs: 3
Switch Inputs are menu selectable for Start, Stop, Reset, Lock, Inhibit, Alarm Acknowledge, Print or Not Used.
Control Input Specifications
Input Scan Rate: 10 scans per second
Logic 1: 4 - 30 VDC
Logic 0: 0 - 0.8 VDC
Input Impedance: 100 K Ω
Control Activation:
Positive Edge or Pos. Level based on product definition for switch usage.

Excitation Voltage

Menu Selectable: 5, 12 or 24 VDC @ 100 mA (fault protected)

Data Logging

The data logger captures print list information to internal storage for approximately 1000 transactions. This information can be used for later uploading or printing. Storage format is selectable for Comma-Carriage Return or Printer formats.

